


**CERTIFICATE OF QUALITY**Page: 1/1  
Date of issue: September 16, 2008

1.	<b>PRODUCT NAME</b> JUBIZOL ADHESIVE (Jubizol lepilo)
2.	<b>GENERAL DESCRIPTION</b> <u>Adhesive mortar</u> for the ETICS JUBIZOL based on EPS, MWP and MWL boards.
3.	<b>COMPOSITION</b> Dry mix cement based mortar with special organic additives.
4.	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>  4.1. APPEARANCE: powder 4.2. COLOUR: grey 4.3. BULK DENSITY (kg/m <sup>3</sup> /20°C): app. 1350 4.4. FLASH POINT: / 4.5. WVTR $\mu$ (-): $\mu < 70$ 4.6. VALUE Sd(m), d= 3 mm: Sd<0,20 ( EN ISO 7783-2, Class 2, medium) 4.7. LIQUID WATER PERMEABILITY (kg/m <sup>2</sup> h <sup>0,5</sup> ): W <sub>24h</sub> <0,10 ( EN 1062 -3, Class 1, low) 4.8. ADHESION TO CONCRETE (EN 24624): >0,5 N/mm <sup>2</sup>
5.	<b>HAZARDS IDENTIFICATION</b> This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC. <b>Xi, IRRITANT</b> , contains cement.
6.	<b>TEST REPORTS</b>  ETA for all types of JUBIZOL ETICS 
7.	<b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b> <b>This construction product is a mineral based render, component of ETICS JUBIZOL due to ETAG 004 and must bear CE-marking. EC Declaration of Conformity is issued.</b>  <b>R&amp;D Coordination Manager</b> <b>Damjan Saksida, B. Sc. Chem. Techn.</b>