

CERTIFICATE OF QUALITY

Page: 1/1
Date of issue: June 16, 2008

1.	PRODUCT NAME Silicate Renders SILICATE TROWELLED RENDER 2,0/2,5 (Silikatni zariban omet) SILICATE SMOOTH RENDER 1,0/1,5/2,0/2,5 (Silikatni glajen omet)
2.	GENERAL DESCRIPTION Exterior waterborne decorative silicate renders (texture coatings).
3.	COMPOSITION Water-based silicone binders, extenders, special additives. Exterior coatings free of ecologically harmful and health hazardous ingredients.
4.	PHYSICAL AND CHEMICAL PROPERTIES 4.1. APPEARANCE: paste 4.2. COLOUR: white, colour shades 4.3. DENSITY (kg/dm ³ /20°C): 1,7 – 2,0 4.4. pH (20°C): 9,5 – 11,5 4.5. FLASH POINT: / 4.6. SOLIDS CONTENT (%): 81 - 88 4.7. DRY FILM THICKNESS (µm): 1,5 – 2,5 mm 4.8. WVTR µ (-): µ <40 4.9. VALUE Sd(m) , d=2 mm: Sd<0,1 (EN ISO 7783-2, Class 1, high) 4.10. LIQUID WATER PERMEABILITY (kg/m ² h ^{0,5}) : W _{24h} <0,1 (EN 1062 –3, Class 3, low) 4.11. ADHESION TO MINERAL RENDER (EN 1542): >0,3 N/mm ²
5.	HAZARDS IDENTIFICATION This product is classified as NOT HAZARDOUS according to EC-directive EU 1999/45/EC.
6.	TEST REPORTS ZAG Ljubljana, Report P 355/02 – 460-5, 14. 06. 2004
7.	The document was issued with the intention to prove the quality of the product according to specific requirements. R&D Coordination Manager Damjan Saksida, B. Sc. Chem. Techn.