

## CERTIFICATE OF QUALITY

Page: 1/1  
Date of issue: June 16, 2008

1.	<p><b>PRODUCT NAME</b> <u>Acrylic Renders</u> <b>ACRYLIC TROWELLED RENDER 2,0/2,5 (Akrilni zariban omet)</b> <b>ACRYLIC SMOOTH RENDER 1,0/1,5/2,0/2,5 (Akrilni glajen omet)</b></p>
2.	<p><b>GENERAL DESCRIPTION</b> Exterior waterborne decorative acrylic renders.</p>
3.	<p><b>COMPOSITION</b> Water based acrylic binders, extenders, pigments, special additives. Water based acrylic emulsion (dispersion) exterior texture coating free of ecologically harmful and health hazardous ingredients.</p>
4.	<p><b>PHYSICAL AND CHEMICAL PROPERTIES</b></p> <p>4.1. APPEARANCE: paste 4.2. COLOUR: white, colour shades 4.3. DENSITY (kg/dm<sup>3</sup>/20°C): 1,6 – 2,1 4.4. pH (20°C): 9,5 – 10,5 4.5. FLASH POINT: / 4.6. SOLIDS CONTENT (%): 72 - 85 4.7. DRY FILM THICKNESS (mm): 1,5 – 2,5 4.8. WVTR μ (-): μ &lt;130 4.9. VALUE Sd(m) , d=2 mm: Sd&lt;0,35 (EN ISO 7783-2, Class 2, medium) 4.10. LIQUID WATER PERMEABILITY (kg/m<sup>2</sup>h<sup>0,5</sup>): W<sub>24h</sub> &lt;0,1, ( EN 1062-3, Class 3, low) 4.11. ADHESION TO MINERAL RENDER: &gt;0,3 N/mm<sup>2</sup> (EN 1542)</p>
5.	<p><b>HAZARDS IDENTIFICATION</b> This product is classified as NOT HAZARDOUS according to EC-directive EU 1999/45/EC.</p>
6.	<p><b>TEST REPORTS</b> ZAG Ljubljana, Report P 355/02 – 460-5, 14. 06. 2004</p>
7.	<p><b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b></p> <p><b>R&amp;D Coordination Manager</b> <b>Damjan Saksida, B. Sc. Chem. Techn.</b></p>