

## CERTIFICATE OF QUALITY

Page: 1/1  
Date of issue: June 16, 2008

|           |   |
|-----------|---|
| <b>1.</b> | <b>PRODUCT NAME</b><br><b>LIME EXTERIOR PAINT (Bio apnena fasadna barva)</b>  |
| <b>2.</b> | <b>GENERAL DESCRIPTION</b><br>Exterior lime paint intended for painting of lime-cement renders. Exterior paint free of ecologically harmful ingredients.  |
| <b>3.</b> | <b>COMPOSITION</b><br>Lime, extenders and special additives.  |
| <b>4.</b> | <b>PHYSICAL AND CHEMICAL PROPERTIES</b><br><br>4.1. APPEARANCE: viscous liquid<br>4.2. COLOUR: white<br>4.3. DENSITY (kg/dm <sup>3</sup> /20°C): app.1,40<br>4.4. pH (20°C): 11,0 – 13,0<br>4.5. FLASH POINT: /<br>4.6. SOLIDS CONTENT (%): 53 – 56<br>4.7. DRY FILM THICKNESS (µm): 100 – 150<br>4.8. WVTR µ (-): µ <300<br>4.9. VALUE Sd(m) , d=100µm: Sd<0,03 (EN ISO 7783-2, Class I: high)<br>4.10. LIQUID WATER PERMEABILITY (kg/m <sup>2</sup> h <sup>0,5</sup> ): W <sub>24h</sub> : 1,6 (EN 1062 –3, Class 1, high)<br>4.11. ADHESION TO MINERAL RENDER (EN ISO 4624): >0,3 N/mm <sup>2</sup><br>4.12. VOC: max. 0,1 g/l |
| <b>5.</b> | <b>HAZARDS IDENTIFICATION</b><br>This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC.<br><b>Xi, IRRITANT</b> , contains lime  |
| <b>6.</b> | <b>TEST REPORTS</b><br>/  |
| <b>7.</b> | <b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b><br><br><b>R&amp;D Coordination Manager</b><br><b>Damjan Saksida, B. Sc. Chem. Techn.</b>  |