

CERTIFICATE OF QUALITY

Page: 1/1
 Date of issue: June 16, 2008

1. PRODUCT NAME	REVITA L COLOR SILIKON Microreinforced Silicon Façade Paint
2. GENERAL DESCRIPTION	Exterior waterborne silicon paint.
3. COMPOSITION	Water based silicone exterior paint free of ecologically harmful and health hazardous ingredients.
4. PHYSICAL AND CHEMICAL PROPERTIES	<p>4.1. APPEARANCE: viscous liquid</p> <p>4.2. COLOUR: white, colour shades</p> <p>4.3. DENSITY (kg/dm³/20°C): app.1,67</p> <p>4.4. pH (20°C): 9,5 – 10,5</p> <p>4.5. FLASH POINT: /</p> <p>4.6. SOLIDS CONTENT (%):69 - 72</p> <p>4.7. DRY FILM THICKNESS (µm): app. 100 -150</p> <p>4.8. WVTR µ (-): µ < 500</p> <p>4.9. VALUE Sd(m) , d=100µm: Sd<0,05 (EN ISO 7783-2, Class 1, high)</p> <p>4.10. LIQUID WATER PERMEABILITY (kg/m²h^{0,5}) : W_{24h} <0,024 (EN 1062 –3, Class 3, low)</p> <p>4.11. ADHESION TO MINERAL RENDER (EN ISO 4624): >0,6 N/mm²</p> <p>4.12. VOC: max. 5 g/l</p>
5. HAZARDS IDENTIFICATION	This product is classified as NOT HAZARDOUS according to EC-directive EU 1999/45/EC.
6. TEST REPORTS	FPL Stuttgart, AT 022/07, 24.05.2007
7. The document was issued with the intention to prove the quality of the product according to specific requirements.	<p>R&D Coordination Manager Damjan Saksida, B. Sc. Chem. Techn.</p>



ISO 9001 Q-159
 ISO 14001 E-034
 OHSAS 18001 H-022

