

## CERTIFICATE OF QUALITY

Page: 1/1  
Date of issue: June 16, 2008

<b>1.</b>	<b>PRODUCT NAME</b> JUBOSIL H Silicone Masonry Water Repellent
<b>2.</b>	<b>GENERAL DESCRIPTION</b> JUBOSIL H is a solvent based siloxane impregnating agent which is used for making mineral building materials, e. g. concrete, lime and lime-cement renders and plasters, lime sandstones, brickwalls and mineral paintings water repellent.
<b>3.</b>	<b>COMPOSITION</b> Jubosil H is based on oligomer siloxanes and organic solvents.
<b>4.</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>  4.1. APPEARANCE: liquid 4.2. COLOUR: colourless 4.3. DENSITY (kg/dm <sup>3</sup> /20°C): app. 0,80 4.4. FLASH POINT: 54 °C 4.5. SOLIDS CONTENT (wt.%): 7,8 – 8,2 4.6. VOC (g/l): max 385
<b>5.</b>	<b>HAZARDS IDENTIFICATION</b> This product is classified as HAZARDOUS according to EC-directive EU 1999/45/EC. <b>Xn, HARMFUL</b> , contains naphta
<b>6.</b>	<b>TEST REPORTS</b> /
<b>7.</b>	<b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b>  <b>R&amp;D Coordination Manager</b> <b>Damjan Saksida, B. Sc. Chem. Techn.</b>