

## CERTIFICATE OF QUALITY

Page : 1/1  
Date of issue : July 05<sup>th</sup>, 2010

<b>1.</b>	<b>PRODUCT NAME</b>  <b>JUBOSIL GF Adhesion Improving Undercoat</b>
<b>2.</b>	<b>GENERAL DESCRIPTION</b> Interior water based adhesion improving undercoat intended for use before applying interior silicate paints to concrete and gypsum based substrate.
<b>3.</b>	<b>COMPOSITION</b> Water – based polymers, extenders, cellulose ether, special additives.
<b>4.</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
4.1.	APPEARANCE : viscous liquid
4.2.	COLOUR : white
4.3.	DENSITY ( kg/dm <sup>3</sup> /20°C ) : app. 1,65
4.4.	pH ( 20°C ) : 9,0 – 10,0
4.5.	FLASH POINT : /
4.6.	SOLID CONTENT ( % ) : 65,0 – 70,0
4.7.	VOC : max. 5 g/l
<b>5.</b>	<b>HAZARDS IDENTIFICATION</b> This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
<b>6.</b>	<b>TEST REPORTS</b> /
<b>7.</b>	<b>The document was issued with the intention to prove the quality of the product according to specific requirements.</b>

R&D Coordination Manager  
Damjan Saksida, B. Sc. Chem. Techn.




JUB d.o.o.  
Dol pri Ljubljani 28  
SI-1262 Dol pri Ljubljani  
Slovenija

10