



MIXER PLUS SMALL MONO - PLASTER 2,2 KW

Continuous mixing pump | reference : 903105200A



Single-phase (230 V) continuous mixing pump, ideal for spraying pre-mixed surface coatings containing lime, cement, finishing compounds, fillers, coloured compounds, adhesives, screeds, etc. and any product compatible with mechanical spraying.

TECHNICAL DATA

Tank capacity	150 L
Power supply	230 V - 50 Hz
Motor thermal protection	sì
Variable speed	3 velocità
Water pressure booster	sì
Flow meter	sì
Water shortage safety device	sì
Spraying flow rate	da 4 a 26 L/min*
Max. spraying distance	40 metri*
Loading height	91 cm
Dimensions (l x w x h)	100 x 76 x 159 cm
Weight	215 kg

Gear motor for mixing chamber	2,2 kW - 320 giri/min
Gear motor for powder scoop wheel	0.25 kW - 10 giri/min
Compressor	reference 8021008000

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Sprinter cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 20 LM neoprene 3x6 power cord
- Adapter + GEKA coupling
- Releasing tool
- Cleaning part
- 25x37 15 LM spray hose with couplings
- 13x19 16 LM air hose with GEKA coupling
- Mixer full spray lance made from aluminium tubing
- Maintenance kit