



## **Continuous mixing pump** | reference : 906000100A



Continuous mixing pump. Mixing is improved thanks to its two separate polyurethane mixing chambers.

The Mixer Remix is suitable for spraying premixed surface coatings containing plaster, lime, cement, finishing compounds, fillers, screeds, resurfacing products, single-layer products, adhesives, etc. and any product compatible with mechanical spraying.

TECHNICAL DATA	
Tank capacity	80 L
Power supply	400 V - 50 Hz
Motor thermal protection	yes
Gear motor for mixing chamber	3 kW
Gear motor for powder scoop wheel	2.2 kW
Variable speed	no
Compressor	9002005000
Water pressure booster	yes
Digital	yes
Water shortage safety device	yes
Spraying flow rate	27 L/min*
Max. spraying distance	40 metres*
Loading height	100 cm
Dimensions (I x w x h)	157 x 60 x 151 cm
Weight	265 kg

(\*) depending on the characteristics of the product used, the stator, the rotor, the diameter and lenght of the hose, the spraying height and the ambient temperature.

## **DELIVERED WITH**

- Anti-seize spray
- Remix cleaning shaft
- 19x26 40 LM water hose with GEKA coupling
- 50 LM neoprene 4x2.5 power cord with plug
- Adapter + GEKA coupling
- Releasing tool
- 35x50 5 LM spray hose with couplings
- 35x50 10 LM spray hose with couplings
- 13x19 5 LM air hose with GEKA coupling
- 13x19 10 LM air hose with GEKA coupling
- Classic spray lance
- Tool bag