



MIXER OPTIMIX 20 - 2,2 KW

Exterior spraying machines | reference : 912000500A



Versatile machine ideal for spraying conventional, pre-mixed surface coatings, special products, cement screed, and decorative coatings.

This machine is compatible with any product with a grain size not exceeding 6 mm, with a setting time of 60 min and a density enabling it to flow through the hose.

TECHNICAL DATA

Tank capacity	80 L
Spraying pressure	0 to 35 bar
Max. pressure	3.5 bar
Max. grain size	6 mm
Dimensions (l x w x h)	140 x 70 x 81 cm
Weight	185 kg

Power supply	230 V - 50 Hz
Motor power	2.2 kW
Compressor flow rate	230 L/min
Variable speed	yes
Compressor motor power	1.1 kW
Spraying flow rate	0 to 17 L/min
Max. spraying distance	25 metres*
Integrated compressor	8021007300

(*) depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- Anti-seize spray
- Two 35x50 10 LM spraying hoses with 1»1/4 couplings
- Classic spray lance - 20 LM neoprene 3x6 power cord with plug
- 13x19 21 LM air hose with GEKA coupling
- Maintenance kit