



Sprayer for slurry, fibrous and decorative surface coatings, etc.

Optimix 40 is a versatile sprayer.

## TECHNICAL CHARACTERISTICS

Tank capacity	100 L (6 x 30 kg bags)
Power supply	230 V - 16 A - 50 Hz
Motor power	2.2 kW / 3 HP
Spraying pressure	0 to 50 bar*
Integrated compressor	yes
Compressor flow rate	366 L/min
Compressor motor power	2.2 kW / 3 HP
Max. compressor pressure	10 bar
Spraying flow rate	0 to 30 kg/min
Integrated vibrator	yes
Max. grain size	3 mm
Dimensions (l x w x h)	130 x 70 x 75 cm
Noise level	96 Lwa
Weight	143 kg

(\*): depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

## DELIVERED WITH

- 1 Ø32 mm x 10 LM hose
- 1 pressure controller with adapter
- 1 EWI spray lance case with:
  - 1 aluminium spray lance for EWI
  - 1 air pressure adjustment
  - 5 spraying nozzles (Ø6, 7, 8, 10 and 12 mm)
  - 3 pointing nozzles (Ø10, 12 and 14 mm)
  - 1 threaded gauge for assembling the beading nozzles
- 2 cleaning balls
- 1 cleaning auger
- 1 Ø7 Allen key