



The Mixer Flatspray 20 is a machine designed for the application of a wide range of surface coatings: skimming plasters, smoothing plasters, multi-purpose surface coatings, droplet-finish surface coatings* and other products.

Mixer Flatspray 20 is fitted with a valveless pump for easy maintenance, a stainless steel round tank and a Ø35 mm drainage hole to facilitate cleaning.

Its large inflatable wheels with their flat profile improve stability and allow the machine to be easily moved, even when the tank is full.

(*with optional droplet-finish kit and compressor)

TECHNICAL CHARACTERISTICS

Tank capacity	4 bags
Power supply	230 V / 16 A / 50 and 60 Hz
Motor power	2.2 kW
Max. operating pressure	100 bar
Max. spraying flow rate	6 L/min*
Max. spraying distance	40 metres*
Pump	volumetric screw pump
Max. nozzle (new)	0.045"
Dimensions (l x w x h)	65 x 74 x 121 cm
Weight	80 kg

(* depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a Ø19 mm x 10 LM hose
- a Ø13 mm x 2.5 LM handling hose
- a one-litre storage fluid bottle
- a case with:
 - a spray lance
 - a TT3 443 nozzle
 - a nozzle carrier
 - two cleaning balls
 - a spray lance brush
 - a 17 mm wrench
 - a 8 mm wrench
 - a cleaning brush