



The Mixer Flatspray 30 is a machine designed for the application of a wide range of surface coatings: skimming plasters, smoothing plasters, multi-purpose surface coatings, droplet-finish surface coatings* and other products.

Mixer Flatspray 30 is fitted with a valveless pump for easy maintenance, a stainless steel round tank and a $\varnothing 35$ mm drainage hole to facilitate cleaning.

Its large inflatable wheels with their flat profile improve stability and allow the machine to be easily moved, even when the tank is full.

(*with optional droplet-finish kit and compressor)

TECHNICAL CHARACTERISTICS

Tank capacity	7 bags
Power supply	230 V / 16 A / 50 and 60 Hz
Motor power	3 kW
Max. operating pressure	120 bar
Max. spraying flow rate	7 L/min*
Max. spraying distance	60 metres*
Pump	volumetric screw pump
Max. nozzle (new)	0.055"
Dimensions (l x w x h)	144 x 64 x 103 cm
Weight	120 kg

(* depending on the characteristics of the product used, the stator, the rotor, the diameter and length of the hose, the spraying height and the ambient temperature.

DELIVERED WITH

- a $\varnothing 19$ mm x 30 LM hose
- a $\varnothing 16$ mm x 2.5 LM handling hose
- a one-litre storage fluid bottle
- a case with:
 - a spray lance
 - a TT3 443 nozzle
 - a nozzle carrier
 - two cleaning balls
 - a spray lance brush
 - a 22 mm wrench
 - a 8 mm wrench
 - a cleaning brush